

FS1580W2-T SPEC CONNECTED WIRELESS GATEWAY

Technology	Smart RF / Wi-Safe 2 / FireAngel Predict®
Power Source	Mains Powered - 5V DC



Remotely monitor and manage safety devices from wherever you are.

- Enables remote real time monitoring without requiring access to properties for complete tenant and asset protection
- Compatible with all FireAngel Specification devices use alongside a network of up to 50 mains and battery FireAngel Specification devices
- **Simple setup and configuration** in seconds grant access to service and maintenance teams, family or friends
- 24/7 compliance when fitted, eliminates any concern over compliance regarding Fire & CO safety
- **Real time notifications** instant access to device diagnostic information is made available with optional device status notifications
- Unique patented technology Intelligent FireAngel Predict® technology accurately monitors device data to pinpoint high fire risks allowing earlier intervention to save lives.
- Secure cloud system device data is completely secure and stored within the FireAngel Cloud
- For complete control, access information via mobile devices Test and silence alarm networks remotely using the free FireAngel Connected App
- · Supplied with a Ethernet network cable
- LED indicators for power supply, network connection, error message

Technical Specification

Dimensions	96mm x 87mm x 23mm
Supply voltage	5V DC / 1AMP (Power supply via enclosed power adapter)
Peak current consumption:	180mA
Technology	Smart RF / Wi-Safe 2 / FireAngel Predict®
Installation positions	Free Standing / Wall Mounted
Warranty	5 years
Weight	80 gm
Independently tested to	EN 300 220-2, EN 301 489-3, EN 301 489-1
Maximum number of connected units	50 Smart RF or Wi-Safe 2 units
Operating frequency	868 MHz
Range	35m (over 200m in clear air)
Data upload	Ethernet
Mobile app compatibility	iOS & Android compatible
Storage and transportation conditions	0°C to +35°C











